

技术资料

短路协调

带塑壳断路器的直接起动器 (50kA-415V IEC60947)

电机		塑壳断路器		接触器	热过载继电器	
(kW)	440V (A)	型号	额定值 I _r (A)	型号	型号	设定范围(A)
5.5	11	GBH (L) 103	16	GMC-32	GTH (K) -40	9~13
7.5	15	GBH (L) 103	16	GMC-32	GTH (K) -40	12~18
10	19	GBH (L) 103	25	GMC-32	GTH (K) -40	18~26
11	21	GBH (L) 103	25	GMC-32	GTH (K) -40	18~26
15	28	GBH (L) 103	32	GMC-32	GTH (K) -40	24~36
18.5	34	GBH (L) 103	40	GMC-75	GTH (K) -85	28~40
22	39	GBH (L) 103	50	GMC-75	GTH (K) -85	34~50
30	54	GBH (L) 103	63	GMC-75	GTH (K) -85	45~65
37	66	GBH (L) 103	80	GMC-75	GTH (K) -85	54~75
45	80	GBH (L) 103	100	GMC-100	GTH(K)-100	65~100
55	99	GBH (L) 103	100	GMC-100	GTH(K)-100	85~125
75	135	GBH (L) 203	160	GMC-150	GTH(K)-150	100~150
90	160	GBH (L) 203	200	GMC-180	GTH(K)-220	120~180
110	192	GBH (L) 203	200	GMC-180	GTH(K)-220	160~240
132	226	GBH (L) 203	250	GMC-220	GTH(K)-220	160~240
160	265	ABH (L) 403b	300	GMC-400	GTH(K)-400	200~300
200	330	ABH (L) 403b	350	GMC-400	GTH(K)-400	260~400
220	353	ABH (L) 403b	400	GMC-400	GTH(K)-400	260~400
250	400	ABS (L) 803b	500	GMC-600	GTH(K)-600	260~400
300	480	ABS (L) 803b	500	GMC-600	GTH(K)-600	400~600

*注：仅磁式

带塑壳断路器的直接起动器 (85kA-415V·IEC60947)

电机		塑壳断路器		接触器	热过载继电器	
(kW)	440V (A)	型号	额定值 I _r (A)	型号	型号	设定范围 (A)
5.5	11	GBH (L) 103	16	GMC-32	GTH (K) -40	9~13
7.5	15	GBH (L) 103	16	GMC-32	GTH (K) -40	12~18
10	19	GBH (L) 103	25	GMC-32	GTH (K) -40	18~26
11	21	GBH (L) 103	25	GMC-32	GTH (K) -40	18~26
15	28	GBH (L) 103	32	GMC-32	GTH (K) -40	24~36
18.5	34	GBH (L) 103	40	GMC-75	GTH (K) -85	28~40
22	39	GBH (L) 103	50	GMC-75	GTH (K) -85	34~50
30	54	GBH (L) 103	63	GMC-75	GTH (K) -85	45~65
37	66	GBH (L) 103	80	GMC-75	GTH (K) -85	54~75
45	80	GBH (L) 103	100	GMC-100	GTH(K)-100	65~100
55	99	GBH (L) 103	100	GMC-100	GTH(K)-100	85~125
75	135	GBH (L) 203	160	GMC-150	GTH(K)-150	100~150
90	160	GBH (L) 203	200	GMC-180	GTH(K)-220	120~180
110	192	GBH (L) 203	200	GMC-180	GTH(K)-220	160~240
132	226	GBH (L) 203	250	GMC-220	GTH(K)-220	160~240
160	265	ABH (L) 403b	300	GMC-400	GTH(K)-400	200~300
200	330	ABH (L) 403b	350	GMC-400	GTH(K)-400	260~400
220	353	ABH (L) 403b	400	GMC-400	GTH(K)-400	260~400
250	400	ABS (L) 803b	500	GMC-600	GTH(K)-600	260~400
300	480	ABS (L) 803b	500	GMC-600	GTH(K)-600	400~600

* 注：表格基于前一范围的组合测试和技术比较。